ddd

ddd

What Does This User Macro Do?

Where Is This Macro Used?

Macro Settings

Macro name:	ddd
Macro has a body:	false
Body processing:	
Output:	Macro generates HTML markup

Source Code

```
## last updated: 9/1/08 by: othomas
#requireResource("confluence.web.resources:scriptaculous")
## Usage: {ask}
## Optional parameters:
##   p1
##   p2
##   p3
##   p4
##   p5
#set ( $p1 = $param0 )
#set ( $p2 = $param1 )
#set ( $p3 = $param2 )
#set ( $p4 = $param3 )
#set ( $p5 = $param4 )
<html>
  <head>

    <script src="http://simile.mit.edu/timeline/api/timeline-api.js" type="text/javascript"></script>

  </head>
  <body onload="onLoad();" onresize="onResize();">
    <div id="my-timeline" style="height: 250px; border: 1px solid #aaa"></div>
  </body>
</html>


<script>
var tl;
function onLoad() {
  var eventSource = new Timeline.DefaultEventSource();
  var bandInfos = [
    Timeline.createBandInfo({
        eventSource:    eventSource,
        date:           "Jun 28 2006 00:00:00 GMT",
        width:          "70%",
        intervalUnit:   Timeline.DateTime.WEEK,
        intervalPixels: 200
    }),
    Timeline.createBandInfo({
        showEventText:  false,
        trackHeight:    0.5,
        trackGap:       0.2,
        eventSource:    eventSource,
        date:           "Jun 28 2006 00:00:00 GMT",
        width:          "30%",
        intervalUnit:   Timeline.DateTime.MONTH,
        intervalPixels: 400
    })
  ];
  bandInfos[1].syncWith = 0;
  bandInfos[1].highlight = true;
  bandInfos[1].eventPainter.setLayout(bandInfos[0].eventPainter.getLayout());

  tl = Timeline.create(document.getElementById("my-timeline"), bandInfos);
  Timeline.loadXML("http://simile.mit.edu/timeline/docs/example1.xml", function(xml, url) {
eventSource.loadXML(xml, url); });
}

var resizeTimerID = null;
function onResize() {
    if (resizeTimerID == null) {
        resizeTimerID = window.setTimeout(function() {
            resizeTimerID = null;
            tl.layout();
        }, 500);
    }
}
</script>
```